


To be used with handle 3901



Art. 3911-P to Art. 3915-P

For general soldering work with propane/oxygen, for calorific value from 9'700 to 38'800 kJ/h, flame temperature max. 2830°C.

Soldering head No 1	Art. 3911-P
Soldering head No 2	Art. 3912-P
Soldering head No 3	Art. 3913-P
Soldering head No 4	Art. 3914-P
Soldering head No 5	Art. 3915-P



Art. 3911-M to Art. 3915-M

For soldering work with natural gas/oxygen, for calorific value from 3'100 to 13'500 kJ/h, flame temperature max. 2785°C.

Soldering head No 1	Art. 3911-M
Soldering head No 2	Art. 3912-M
Soldering head No 3	Art. 3913-M
Soldering head No 4	Art. 3914-M
Soldering head No 5	Art. 3915-M



Art. 3910-H to Art. 3913-H

For soldering work with hydrogen/oxygen, for calorific value from 2'900 to 9'400 kJ/h, flame temperature max. 2855°C.

Soldering head No 0	Art. 3910-H
Soldering head No 1	Art. 3911-H
Soldering head No 2	Art. 3912-H
Soldering head No 3	Art. 3913-H



Art. 3932-P to Art. 3934-P

Flexible welding heads of soft copper for welding areas which are difficult to reach (e.g. pipe work), length approx.. 230 mm

Flexible welding head	1 – 2 mm	Art. 3932-P
Flexible welding head	2 – 4 mm	Art. 3933-P
Flexible welding head	4 – 6 mm	Art. 3934-P

The front sections of the flexible heads are also available separately:
 to Art. 3932-P Art. 39402-P
 to Art. 3933-P Art. 39403-P
 to Art. 3934-P Art. 39404-P

Art. 3965



Micro soldering/brazing head for very fine precise soldering applications, universally adjustable, for oxy-fuel gas (with the exception of acetylene), complete with 3 interchangeable needle-tips Art. 3965



Art. 3960

Heating head with crown-shaped flame for propane/natural gas and oxygen. The ideal torch head for the rapid melting of hot surfacing alloys Art. 3960



Art. 3940

Brazing head with ring-shaped flame for propane/natural gas and oxygen. Proved brazing head with three interchangeable nozzles; very stable flame for fine, medium and big size flames. Also suitable for the soldering of chromium-cobalt alloys. Art. 3940

Nozzle No 1	Art. 3937
Nozzle No 2	Art. 3938
Nozzle No 3	Art. 3939

To be used with handle 3601



Art. 3610-P to Art. 3618-P

Soldering head no 1
Soldering head no 2
Soldering head no 3
Soldering head no 4
Soldering head no 5
Soldering head no 6
Soldering head no 7
Soldering head no 8

Art. 3611-P
Art. 3612-P
Art. 3613-P
Art. 3614-P
Art. 3615-P
Art. 3616-P
Art. 3617-P
Art. 3618-P



Art. 3632-P to Art. 3634-P

Flexible welding heads of soft copper for welding areas which are difficult to reach (e.g. pipe work), length approx. 230 mm

Flexible soldering head 1 – 2 mm
Flexible soldering head 2 – 4 mm
Flexible soldering head 4 – 6 mm

Art. 3632-P
Art. 3633-P
Art. 3634-P

The front sections of the flexible heads are also available separately:

to Art. 3632-P
to Art. 3633-P
to Art. 3634-P

Art. 36402-P
Art. 36403-P
Art. 36404-P