

PIPE CUTTING MACHINES

tubOcut II and III

For cutting and bevelling of steel pipes with outer diameters
from 110 mm (4,3“) to 260 mm (10,2“) tubOcut II
from 250 mm (9,8“) to 410 mm (16,1“) tubOcut III



Features of the tubOcut II and III

- Outstanding guidance and cutting precision
- Easy mounting and operation
- Robust and solid in construction
- Excellent cutting quality

Thus, the machines are also perfectly suited for the use on construction sites

GLOOR



- Fast and easy mounting of the two semi-circular steel guides
- Precise centering and locking onto the pipe by means of a special clamping device
- Very high guidance and cutting precision through the three-point support of the guide and drive wheels
- Possibility of bevel cutting up to 45° with the aid of an angle scale at the torch holder

Scope of supply:

- set of block nozzles 3 - 50 mm for acetylene or propane
- nozzle cleaners
- spanners

Technical data:

	tubOcut II	tubOcut III
Article numbers	: Art. 7320	Art. 7330
Minimum pipe diameter	: 110 mm (4,3")	250 mm (9,8")
Maximum pipe diameter	: 260 mm (10,2")	410 mm (16,1")
Weight	: 13.2 kg	15.4 kg
Cutting range	: 3 - 50 mm	3 - 50 mm
Fuel gas	: acetylene or propane – please specify in your order	